

View Online at <https://aerobasegroup.com/nsn/5950-00-284-5695>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.250 inches single mounting facility single center group

Mounting Hole Diameter:

0.228 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.875 inches

Body Width:

6.875 inches

Body Height:

4.906 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

8.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

6.40 ac volts single component 2nd secondary

Special Features:

Case metal material, w/two rows of three mtg holes ea spaced 2.625 in. C to c in row

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0