

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7489>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.6 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.375 inches

Body Width:

2.500 inches

Body Height:

2.687 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

20.0 milliamperes ac single component single secondary

Winding Operating Voltage:

650.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0