

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7504>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.063 inches single mounting facility single center group4.063 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.938 inches single mounting facility single center group3.938 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

5.063 inches 5.063 inches

Body Width:

4.313 inches 4.313 inches

Body Height:

4.000 inches 4.000 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

12.0 amperes ac single component 4th secondary

Winding Operating Voltage:

850.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0