

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7540>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group0.188 inches single group0.188 inches single group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Body Length:

3.750 inches 3.750 inches 3.750 inches

Body Width:

3.250 inches 3.250 inches 3.250 inches

Body Height:

4.688 inches 4.688 inches 4.688 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and slot single groupslot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Power Rating:

110.0 volts-amperes single component single secondary

Winding Operating Voltage:

107.00 ac volts single component single primary and 11.00 ac volts single component single secondary117.00 ac volts single component single primary

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: