

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7561>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

3.812 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

3 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

85.0 milliamperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component 2nd primary 115.00 ac volts single component 1st primary

Special Features:

3primary windings; third primary 95 cycles 50.8 v with center tap; 1secondary winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0