

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7561>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

2.750 inches

**Body Width:**

2.375 inches

**Body Height:**

3.812 inches

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

3 primary single component and 1 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

85.0 milliamperes dc single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component 2nd primary 115.00 ac volts single component 1st primary

**Special Features:**

3primary windings; third primary 95 cycles 50.8 v with center tap; 1secondary winding

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0