

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7562>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group2.688 inches single mounting facility single center group

Overall Height:

5.344 inches 5.344 inches

Frequency Rating:

40.0 hertz single component and 40.0 hertz single component and 450.0 hertz single component450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 4.187 inches and 4.187 inches and 4.312 inches 4.312 inches

Body Width:

Between 3.563 inches and 3.563 inches and 3.688 inches 3.688 inches

Body Height:

Between 4.375 inches and 4.375 inches and 4.500 inches 4.500 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

100.0 milliamperes ac single component single secondary

Winding Operating Voltage:

960.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

3 standoff insulator and 4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0