

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7576>

Reliability Indicator:

Not established

Overall Length:

Between 3.687 inches and 3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.225 inches single mounting facility single center group and 3.275 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.600 inches single mounting facility single center group and 2.650 inches single mounting facility single center group

Overall Height:

4.000 inches

Overall Width:

Between 3.062 inches and 3.125 inches

Frequency Rating:

49.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

70.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

64.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

5.10 ac volts single component 3rd secondary 14.50 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0