

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7785>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility single center group3.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

**Frequency Rating:**

49.0 hertz single component and 49.0 hertz single component and 65.0 hertz single component65.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

3.750 inches 3.750 inches

**Body Width:**

3.125 inches 3.125 inches

**Body Height:**

4.000 inches 4.000 inches

**Inclosure Type:**

Openopen

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

2 primary single component and 2 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

6.4 amperes ac single component 4th secondary

**Winding Operating Voltage:**

230.00 ac volts single component 2nd primary115.00 ac volts single component 1st primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0