

View Online at <https://aerobasegroup.com/nsn/5950-00-295-7785>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Frequency Rating:

49.0 hertz single component and 49.0 hertz single component and 65.0 hertz single component65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.750 inches 3.750 inches

Body Width:

3.125 inches 3.125 inches

Body Height:

4.000 inches 4.000 inches

Inclosure Type:

Openopen

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

6.4 amperes ac single component 4th secondary

Winding Operating Voltage:

230.00 ac volts single component 2nd primary115.00 ac volts single component 1st primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0