## NSN 5950-00-295-8014

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-295-8014

| Reliability Indicator:                          |   |
|---|---|
| Not established                                 |   |
| Center To Center Distance Between Mount         | ing Facilities Parallel To Length:  |
| 4.875 inches single mounting facility single ce | inter group   |
| Center To Center Distance Between Mount         | ing Facilities Parallel To Width:   |
| 4.875 inches single mounting facility single ce | inter group   |
| Frequency Rating:                               |   |
| 50.0 hertz single component or 60.0 hertz sir   | igle component  |
| nput-output Phase Relationship:                 |   |
| Single phase to single phase single componer    | nt  |
| Winding Shielding Method:                       |   |
| nternal shield grounded to inclosure single co  | mponent   |
| Body Length:                                    |   |
| 5.781 inches                                    |   |
| Body Width:                                     |   |
| 5.781 inches                                    |   |
| Body Height:                                    |   |
| 7.000 inches                                    |   |
| nclosure Type:                                  |   |
| Hermetically sealed                             |   |
| Mounting Facility Quantity:                     |   |
| 1 single group                                  |   |
| Mounting Method:                                |   |
| Threaded stud single group                      |   |
| Winding Function And Quantity:                  |   |
| primary single component and 1 secondary        | single component  |
| Thready Qty Per Inch (tpi):                     |   |
| 20 single group                                 |   |
| Fhread Size:                                    |   |
| 0.250 inches single group                       |   |
| Winding Operating Current:                      |   |
| 250.0 milliamperes ac single component sing     | le secondary  |
| Winding Operating Voltage:                      |   |
| 15.00 ac volts single component single prim     | ary and 870.00 ac volts single component single secondary125.00 ac volts single component |
| single primary                                  |   |
| Thread Series Designator:                       |   |
| Jnc single group                                |   |
| Ferminal Type And Quantity:                     |   |
| 6 standoff, solder lug                          |   |
| Shelf Life:                                     |   |
| N/a   |   |
| Jnit Of Measure:                                |   |

## NSN 5950-00-295-8014

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

