## NSN 5950-00-295-8037

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-295-8037 **Reliability Indicator:** Not established Frequency Rating: 320.0 hertz single component and 1.76 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component **Body Length:** 2.812 inches **Body Width:** 2.812 inches **Body Height:** 3.750 inches **Distance Between Mounting Facility Centers:** 1.750 inches single mounting facility single center group **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 2 single group **Mounting Method:** Threaded stud single group **Winding Function And Quantity:** 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group **Winding Operating Current:** 50.0 milliamperes ac single component 2nd secondary and 67.0 milliamperes ac single component 2nd secondary **Winding Operating Voltage:** 108.00 ac volts single component 1st secondary and 850.00 ac volts single component 2nd secondary630.00 ac volts single component 1st secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 9 tab, solder lug Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5950-00-295-8037

Power Transformer - Page 2 of 2



Fiig:

A058b0