

View Online at <https://aerobasegroup.com/nsn/5950-00-295-8037>

Reliability Indicator:

Not established

Frequency Rating:

320.0 hertz single component and 1.76 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.812 inches

Body Width:

2.812 inches

Body Height:

3.750 inches

Distance Between Mounting Facility Centers:

1.750 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

50.0 milliamperes ac single component 2nd secondary and 67.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

108.00 ac volts single component 1st secondary and 850.00 ac volts single component 2nd secondary 630.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0