## NSN 5950-00-295-8040

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-295-8040                               |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                   |
| 3.688 inches single mounting facility single center group                                   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                    |
| 3.000 inches single mounting facility single center group                                   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                                      |
| Body Length:  |
| 4.688 inches  |
| Body Width:   |
| 4.000 inches  |
| Body Height:  |
| 6.000 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 2 secondary single component                                 |
| Thready Qty Per Inch (tpi):   |
| 20 single group   |
| Thread Size:  |
| 0.250 inches single group   |
| Winding Operating Current:  |
| 23.0 amperes ac single component 1st secondary  |
| Winding Operating Voltage:  |
| 2.50 ac volts single component all secondary117.00 ac volts single component single primary |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 8 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

## NSN 5950-00-295-8040

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0