NSN 5950-00-295-8209

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-295-8209

| Reliability Indicator: |
|-------------------------------------------------------------------------------------------------------------------------------------------|
| Not established |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 29.20 millihenries single component single winding and 119.20 millihenries single component single winding and 477.00 millihenries single |
| component single winding and 1.322 henry single component single winding |
| Body Length: |
| 2.281 inches |
| Body Outside Diameter: |
| 1.594 inches |
| Distance Between Mounting Facility Centers: |
| 1.312 inches single mounting facility single center group |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Dc Resistance Rating In Ohms: |
| 77.300 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 5 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |