

View Online at <https://aerobasegroup.com/nsn/5950-00-295-8346>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.312 inches

Body Width:

2.000 inches

Body Height:

2.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Cubic Measure (non-core):

9.7 cubic inches

Winding Tap Location (non-core):

Tap w/o center tap single component single primary output

Winding Operating Current:

1.4 amperes ac single component single primary output

Winding Power Rating:

380.0 volts-amperes single component single primary input

Winding Operating Voltage:

27.00 ac pounds per hour wet single component single primary output

Terminal Type And Quantity:

3 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0