

View Online at <https://aerobasegroup.com/nsn/5950-00-295-8596>

**Reliability Indicator:**

Not establishednot establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.234 inches single mounting facility single center group and 2.234 inches single mounting facility single center group and 2.234 inches single mounting facility single center group and 2.266 inches single mounting facility single center group2.266 inches single mounting facility single center group2.266 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.109 inches single mounting facility single center group and 2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group2.141 inches single mounting facility single center group2.141 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

**Maximum Transformer Power Rating:**

130.0 volt-ampere single component130.0 volt-ampere single component130.0 volt-ampere single component

**Body Length:**

2.969 inches 2.969 inches 2.969 inches

**Body Width:**

2.781 inches 2.781 inches 2.781 inches

**Body Height:**

3.938 inches 3.938 inches 3.938 inches

**Maximum Operating Temp:**

150.0 degrees celsius150.0 degrees celsius150.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

**Thread Size:**

0.164 inches single group0.164 inches single group0.164 inches single group

**Winding Operating Current:**

600.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

17.60 ac volts single component single primary and 6.30 ac volts single component single secondary6.30 ac volts single component single secondary35.00 ac volts single component single primary and 47.60 ac volts single component single primary and 127.60 ac volts single component single primary and 214.60 ac volts single component single primary and 242.60 ac volts single component single primary and 542.60 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Demilitarization:**

No

**Fig:**

A058b0