

View Online at <https://aerobasegroup.com/nsn/5950-00-295-8596>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.234 inches single mounting facility single center group and 2.234 inches single mounting facility single center group and 2.234 inches single mounting facility single center group and 2.266 inches single mounting facility single center group2.266 inches single mounting facility single center group2.266 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.109 inches single mounting facility single center group and 2.109 inches single mounting facility single center group and 2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group2.141 inches single mounting facility single center group2.141 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Maximum Transformer Power Rating:

130.0 volt-ampere single component130.0 volt-ampere single component130.0 volt-ampere single component

Body Length:

2.969 inches 2.969 inches 2.969 inches

Body Width:

2.781 inches 2.781 inches 2.781 inches

Body Height:

3.938 inches 3.938 inches 3.938 inches

Maximum Operating Temp:

150.0 degrees celsius150.0 degrees celsius150.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group0.164 inches single group

Winding Operating Current:

600.0 milliamperes ac single component single secondary

Winding Operating Voltage:

17.60 ac volts single component single primary and 6.30 ac volts single component single secondary6.30 ac volts single component single secondary35.00 ac volts single component single primary and 47.60 ac volts single component single primary and 127.60 ac volts single component single primary and 214.60 ac volts single component single primary and 242.60 ac volts single component single primary and 542.60 ac volts single component single primary

Thread Series Designator:

Unc single group

Demilitarization:

No

Fiig:

A058b0