

View Online at <https://aerobasegroup.com/nsn/5950-00-299-1888>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.370 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.120 inches single mounting facility single center group and 1.140 inches single mounting facility single center group

Mounting Hole Diameter:

0.153 inches single group and 0.159 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.130 inches

Body Width:

1.940 inches

Body Height:

2.070 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

50.0 milliamperes dc single component 2nd secondary

Winding Power Rating:

3.9 volts-amperes single component 3rd secondary

Winding Operating Voltage:

9.00 ac volts single component 1st secondary

Terminal Type And Quantity:

9 tab, solder lug

Specification Data:

07217-623210 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0