

View Online at <https://aerobasegroup.com/nsn/5950-00-300-1957>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Overall Width:

2.750 inches 2.750 inches

Mounting Hole Diameter:

0.148 inches single group and 0.148 inches single group and 0.165 inches single group0.165 inches single group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component and three phase to three phase single component and three phase to single phase single componentthree phase to single phase single component

Transformer Winding Connection Type:

Delta-deltadelta-delta

Winding Shielding Method:

Internally shielded single componentinternally shielded single component

Body Length:

3.630 inches 3.630 inches

Body Height:

1.480 inches 1.480 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

Winding Operating Current:

1.0 amperes dc single component 3rd secondary

Winding Operating Voltage:

38.00 ac volts single component 3rd secondary and 21.50 ac volts single component 2nd secondary and 42.00 ac volts single component 3rd secondary24.50 ac volts single component 2nd secondary

Special Features:

1primary, 5 secondaries; all currents are stated as rectified; 5th secondary ratings are the same as 4th secondary

Terminal Type And Quantity:

18 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0