

View Online at <https://aerobasegroup.com/nsn/5950-00-300-1957>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Overall Width:**

2.750 inches 2.750 inches

**Mounting Hole Diameter:**

0.148 inches single group and 0.148 inches single group and 0.165 inches single group0.165 inches single group

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component and three phase to three phase single component and three phase to single phase single componentthree phase to single phase single component

**Transformer Winding Connection Type:**

Delta-deltadelta-delta

**Winding Shielding Method:**

Internally shielded single componentinternally shielded single component

**Body Length:**

3.630 inches 3.630 inches

**Body Height:**

1.480 inches 1.480 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

**Winding Operating Current:**

1.0 amperes dc single component 3rd secondary

**Winding Operating Voltage:**

38.00 ac volts single component 3rd secondary and 21.50 ac volts single component 2nd secondary and 42.00 ac volts single component 3rd secondary24.50 ac volts single component 2nd secondary

**Special Features:**

1primary, 5 secondaries; all currents are stated as rectified; 5th secondary ratings are the same as 4th secondary

**Terminal Type And Quantity:**

18 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0