

View Online at <https://aerobasegroup.com/nsn/5950-00-301-3734>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Overall Width:**

2.750 inches 2.750 inches

**Mounting Hole Diameter:**

0.148 inches single group and 0.148 inches single group and 0.165 inches single group0.165 inches single group

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component and three phase to three phase single component and three phase to single phase single componentthree phase to single phase single component

**Transformer Winding Connection Type:**

Delta-deltadelta-delta

**Winding Shielding Method:**

Internally shielded single componentinternally shielded single component

**Body Length:**

3.630 inches 3.630 inches

**Body Height:**

1.630 inches 1.630 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 7 secondary single component7 secondary single component

**Winding Operating Current:**

3.0 amperes dc single component 1st secondary

**Winding Operating Voltage:**

184.00 ac volts single component single primary and 184.00 ac volts single component single primary and 216.00 ac volts single component single primary216.00 ac volts single component single primary

**Special Features:**

1primary, 7 secondary windings; all currents are shown as rectified; secondaries 6 and 7 are rated the same, 0.1 amp dc at 16.5 and 19.5 volts rms; 5th secondary is 0.57 amps at 21.50 and 24.50 volts rms1primary, 7 secondary windings; all currents are shown as rectified; secondaries 6 and 7 are rated the same, 0.1 amp dc at 16.5 and 19.5 volts rms; 5th secondary is 0.57 amps at 21.50 and 24.50 volts rms

**Terminal Type And Quantity:**

24 tab, solder lug

**Shelf Life:**

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0