NSN 5950-00-303-5436

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-303-5436

| Reliability Indicator: |
|---|
| Not established |
| Overall Height: |
| 3.126 inches |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 130.00 millihenries single component single winding and 650.00 millihenries single component single winding |
| Frequency Rating: |
| 800.0 hertz single component |
| Body Length: |
| 2.656 inches |
| Body Width: |
| 2.344 inches |
| Body Height: |
| 2.438 inches |
| Maximum Operating Temp: |
| 160.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 1.250 inches single mounting facility single center group |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 24 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 0.1 milliamperes dc single component single winding and 0.5 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 23.000 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |

2 standoff, solder lug

NSN 5950-00-303-5436

Reactor - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0