NSN 5950-00-303-5446

Power Transformer - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-00-303-5446
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.875 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.500 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
3.656 inches
Body Width:
2.281 inches
Body Height:
4.031 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
3.0 amperes ac single component 2nd secondary
Winding Operating Voltage:
980.00 ac volts single component 3rd secondary6.40 ac volts single component 2nd secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
12 solder stud
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-00-303-5446

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0