



View Online at <https://aerobasegroup.com/nsn/5950-00-304-8602>

Reliability Indicator:

Not establishednot established

Overall Length:

1.665 inches 1.665 inches

Overall Width:

1.150 inches 1.150 inches

Mounting Hole Diameter:

0.120 inches single group and 0.120 inches single group and 0.160 inches single group0.160 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 1.105 inches and 1.105 inches and 1.125 inches 1.125 inches

Body Width:

1.060 inches 1.060 inches

Body Height:

0.840 inches 0.840 inches

Distance Between Mounting Facility Centers:

1.365 inches single mounting facility single center group and 1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group1.385 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

500.0 milliamperes ac single component single primary

Winding Operating Voltage:

34.00 ac volts single component single secondary115.00 ac volts single component single primary

Test Data Document:

94117-243151+1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 tab, solder lug

Specification Data:

94117-243151+1 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0