

View Online at <https://aerobasegroup.com/nsn/5950-00-306-3257>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.032 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.687 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.900 inches

Body Width:

1.317 inches

Body Height:

1.455 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

150.0 milliamperes ac single component all secondary

Winding Operating Voltage:

38.00 ac volts single component all secondary 115.00 ac volts single component single primary

Special Features:

1 turret terminal provided to ground inclosure

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 wire hook and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0