

View Online at <https://aerobasegroup.com/nsn/5950-00-308-5097>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.875 inches

Body Width:

3.125 inches

Body Height:

1.625 inches

End Application:

Los angeles class ssn (688); sturgeon class ssn (637); ticonderoga class cg (47); virginia class cgn (41); spruance class dd (963); cvn 68 class reactor fill aux; Forrestal class cv; nimitz class cvn

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

6.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

8.30 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 tab, solder lug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0