

View Online at <https://aerobasegroup.com/nsn/5950-00-310-4072>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.620 inches single mounting facility single center group and 3.630 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.245 inches single mounting facility single center group and 2.255 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.125 inches

Body Width:

2.750 inches

Body Height:

2.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

20.0 milliamperes dc single component 1st secondary

Winding Power Rating:

127.7 volts-amperes single component 3rd secondary32.6 volts-amperes single component 4th secondary127.7 volts-amperes single component 3rd secondary

Winding Operating Voltage:

23.60 dc volts single component 2nd secondary10.30 dc volts single component 3rd secondary23.60 dc volts single component 2nd secondary

Special Features:

One primary winding and six secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

25 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0