

View Online at <https://aerobasegroup.com/nsn/5950-00-313-4571>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Transformer Function:

Output

Impedance Rating In Ohms:

0.6 single component single secondary

Frequency Rating:

100.0 hertz single component and 1.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 20 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.250 inches

Body Width:

1.875 inches

Body Height:

3.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

50.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0