NSN 5950-00-314-3631

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-314-3631

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group2.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group1.859 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.063 inches 3.063 inches

Body Width:

2.625 inches 2.625 inches

Body Height:

3.188 inches 3.188 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thread Size:

0.164 inches single group 0.164 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

42.00 ac volts single component 2nd secondary26.00 ac volts single component 4th secondary26.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-00-314-3631

Power Transformer - Page 2 of 2



Fiig:

A058b0