

View Online at <https://aerobasegroup.com/nsn/5950-00-318-2364>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.802 inches single mounting facility single center group and 2.802 inches single mounting facility single center group and 2.832 inches single mounting facility single center group2.832 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.240 inches single mounting facility single center group and 2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group2.260 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

Between 3.740 inches and 3.740 inches and 3.760 inches 3.760 inches

Body Width:

Between 3.370 inches and 3.370 inches and 3.390 inches 3.390 inches

Body Height:

Between 2.270 inches and 2.270 inches and 2.290 inches 2.290 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

50.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

25.10 ac volts single component 1st secondary and 32.90 ac volts single component 1st secondary and 58.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0