## NSN 5950-00-318-2433

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-318-2433

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.125 inches single mounting facility single center group

### **Mounting Hole Diameter:**

0.154 inches single group

### **Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

Between 2.055 inches and 2.065 inches

### **Body Width:**

Between 1.495 inches and 1.505 inches

### **Body Height:**

Between 1.745 inches and 1.755 inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Flange single group and unthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

### **Winding Operating Current:**

300.0 milliamperes ac single component 2nd secondary

### **Winding Operating Voltage:**

46.00 ac volts single component 2nd secondary

### **Terminal Type And Quantity:**

7 tab, solder lug

### Shelf Life:

N/a

### **Unit Of Measure:**

--

### **Demilitarization:**

No

# NSN 5950-00-318-2433

Power Transformer - Page 2 of 2



Fiig:

A058b0