NSN 5950-00-318-2433

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-318-2433

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.154 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 2.055 inches and 2.065 inches

Body Width:

Between 1.495 inches and 1.505 inches

Body Height:

Between 1.745 inches and 1.755 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

300.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

46.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5950-00-318-2433

Power Transformer - Page 2 of 2



Fiig:

A058b0