## NSN 5950-00-318-6297

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-318-6297

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group and 2.250 inches single mounting facility single center group and 2.250 inches

single mounting facility single center group2.250 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group2.750 inches single mounting facility single center group

#### Mounting Hole Diameter:

0.281 inches single group0.281 inches single group

#### **Frequency Rating:**

57.0 hertz single component and 57.0 hertz single component and 57.0 hertz single component57.0 hertz single component

#### Input-output Phase Relationship:

Three phase to six phase single componentthree phase to six phase single component

#### **Body Length:**

11.500 inches 11.500 inches

#### **Body Width:**

3.500 inches 3.500 inches

#### Body Height:

8.500 inches 8.500 inches

### Inclosure Type:

Openopen

#### **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group20 single group

#### Thread Size:

0.250 inches single group0.250 inches single group

#### Winding Operating Current:

146.0 amperes ac single component single secondary

#### Winding Power Rating:

2.34 kilovolt-amperes single component single secondary

#### Winding Operating Voltage:

208.00 ac volts single component single primary

#### **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

12 threaded hole

### Shelf Life:

NI/o

# NSN 5950-00-318-6297

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

