

View Online at <https://aerobasegroup.com/nsn/5950-00-320-7443>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.938 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

3.000 inches

Body Width:

1.500 inches

Body Height:

2.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

30.0 milliamperes ac single component single secondary and 100.0 milliamperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary 60.00 ac volts single component single secondary and 270.00 ac volts single component single secondary and 430.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0