

View Online at <https://aerobasegroup.com/nsn/5950-00-320-7726>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

3.750 inches 3.750 inches

Body Width:

3.500 inches 3.500 inches

Body Height:

2.250 inches 2.250 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Bushing single groupbushing single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

1250.0 milliamperes dc single component single secondary

Winding Operating Voltage:

117.00 ac volts single component single primary27.00 ac volts single component single secondary and 54.00 ac volts single component single secondary

Special Features:

Currents are stated as rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0