

View Online at <https://aerobasegroup.com/nsn/5950-00-324-0267>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

3.000 inches 3.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Overall Width:**

3.000 inches 3.000 inches

**Mounting Hole Diameter:**

0.380 inches single group0.380 inches single group

**Frequency Rating:**

15.0 kilohertz single component15.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Height:**

1.780 inches 1.780 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 7 secondary single component7 secondary single component

**Winding Operating Current:**

6.0 amperes dc single component 4th secondary

**Winding Operating Voltage:**

4.24 ac volts single component 1st secondary4.24 ac volts single component 1st secondary

**Special Features:**

Third and fourth secondaries have the current and voltage rectified; also the transformer consist of one primary and seven secondary windings  
third and fourth secondaries have the current and voltage rectified; also the transformer consist of one primary and seven secondary windings

**Terminal Type And Quantity:**

24 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0