## NSN 5950-00-324-0267

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-324-0267

#### **Reliability Indicator:**

Not establishednot established

#### **Overall Length:**

3.000 inches 3.000 inches

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

#### **Overall Width:**

3.000 inches 3.000 inches

#### **Mounting Hole Diameter:**

0.380 inches single group 0.380 inches single group

#### Frequency Rating:

15.0 kilohertz single component15.0 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

#### **Body Height:**

1.780 inches 1.780 inches

## **Maximum Operating Temp:**

130.0 degrees celsius 130.0 degrees celsius

#### **Inclosure Type:**

Fully enclosedfully enclosed

## **Mounting Facility Quantity:**

4 single group4 single group

## **Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 primary single component and 7 secondary single component 7 secondary single component

## **Winding Operating Current:**

6.0 amperes dc single component 4th secondary

#### **Winding Operating Voltage:**

4.24 ac volts single component 1st secondary4.24 ac volts single component 1st secondary

#### **Special Features:**

Third and fourth secondaries have the current and voltage rectified; also the transformer consist of one primary and seven secondary windingsthird and fourth secondaries have the current and voltage rectified; also the transformer consist of one primary and seven secondary windings

### **Terminal Type And Quantity:**

24 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-324-0267

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0