

View Online at <https://aerobasegroup.com/nsn/5950-00-324-2967>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

2.750 inches 2.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.438 inches single mounting facility single center group1.438 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.406 inches single mounting facility single center group1.406 inches single mounting facility single center group

**Overall Height:**

3.000 inches 3.000 inches

**Overall Width:**

2.000 inches 2.000 inches

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Maximum Operating Temp:**

85.0 degrees celsius85.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

4.5 amperes ac single component single secondary and 12.0 amperes ac single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary6.30 ac volts single component single secondary6.30 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0