

View Online at <https://aerobasegroup.com/nsn/5950-00-326-1814>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.109 inches all mounting facilities single center group and 2.141 inches all mounting facilities single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.734 inches all mounting facilities single center group and 1.766 inches all mounting facilities single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

3.812 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.138 inches all groupings

Winding Operating Current:

700.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

25.40 ac volts single component 1st secondary 30.90 ac volts single component 3rd secondary 125.00 ac volts single component 2nd secondary

Test Data Document:

10001-2928145 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

16 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0