# NSN 5950-00-328-1041

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-328-1041

# **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

#### Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

2.720 inches 2.720 inches

#### **Body Width:**

1.500 inches 1.500 inches

#### **Body Height:**

2.000 inches 2.000 inches

#### **Maximum Operating Temp:**

85.0 degrees celsius85.0 degrees celsius

#### **Inclosure Type:**

Fully enclosedfully enclosed

# **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thread Size:

0.112 inches single group

#### **Winding Operating Current:**

75.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

191.00 ac volts single component single secondary115.00 ac volts single component single primary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

4 turret

#### Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

No

# NSN 5950-00-328-1041

Power Transformer - Page 2 of 2



Fiig:

A058b0