# NSN 5950-00-328-1046

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-328-1046

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

#### Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Three phase to six phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

4.250 inches

#### **Body Width:**

3.500 inches

### **Body Height:**

2.620 inches

# **Maximum Operating Temp:**

85.0 degrees celsius

# **End Application:**

E-2c hawkeye aircraft. Velocity pool reparable piece parts.

#### **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.164 inches single group

# **Winding Operating Current:**

33.0 amperes dc single component single secondary

#### **Criticality Code Justification:**

Feat

# **Winding Operating Voltage:**

186.20 ac volts single component single primary and 196.00 ac volts single component single primary and 205.80 ac volts single component single primary

#### **Special Features:**

Weapon system essential

# **Thread Series Designator:**

Unc single group

# NSN 5950-00-328-1046

Power Transformer - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0