NSN 5950-00-328-1046

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-328-1046

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.250 inches

Body Width:

3.500 inches

Body Height:

2.620 inches

Maximum Operating Temp:

85.0 degrees celsius

End Application:

E-2c hawkeye aircraft. Velocity pool reparable piece parts.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

33.0 amperes dc single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

186.20 ac volts single component single primary and 196.00 ac volts single component single primary and 205.80 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

NSN 5950-00-328-1046

Power Transformer - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0