NSN 5950-00-329-5508

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-329-5508

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.875 inches

Body Width:

2.250 inches

Body Height:

2.500 inches

Maximum Operating Temp:

85.0 degrees celsius

End Application:

E-2c hawkeye aircraft

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

2.2 amperes ac single component single primary

Criticality Code Justification:

Feat

Winding Operating Voltage:

4.50 ac volts single component single secondary and 107.50 ac volts single component single primary and 10.30 ac volts single component single secondary119.50 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

NSN 5950-00-329-5508

Power Transformer - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	------	-----	-----------

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0