

View Online at <https://aerobasegroup.com/nsn/5950-00-329-5719>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single componentthree phase to six phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

5.810 inches 5.810 inches

Body Width:

4.190 inches 4.190 inches

Body Height:

3.060 inches 3.060 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

7.2 amperes ac single component 1st secondary

Winding Operating Voltage:

8.36 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

32 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0