## NSN 5950-00-329-7601

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-329-7601   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 3.437 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.750 inches single mounting facility single center group   |
| Frequency Rating:   |
| 48.0 hertz single component and 62.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Core grounded and brought out to terminal single component and internal shield brought out to terminal single component |
| Body Length:  |
| 4.437 inches  |
| Body Width:   |
| 3.250 inches  |
| Body Height:  |
| 3.375 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 2 primary single component and 4 secondary single component   |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Operating Current:  |
| 80.0 milliamperes ac single component 4th secondary   |
| Winding Operating Voltage:  |
| 7.00 ac volts single component 3rd secondary154.00 ac volts single component 2nd secondary                              |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 16 wire lead  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
|   |

## NSN 5950-00-329-7601

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

