

View Online at <https://aerobasegroup.com/nsn/5950-00-332-5972>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.940 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.750 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.810 inches

Body Width:

4.440 inches

Body Height:

5.310 inches

End Application:

Helicopter, uscg search and rescue, hh-60j; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; aircraft, viking s-3b; helicopter, mh-53e; aircraft, c-2a (reprocured); aircraft, tomcat f-14; aircraft, hawkkeye e-2c; helicopter, advance attack, ah-1w

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

5 single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

23.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0