# NSN 5950-00-333-0266

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-333-0266

# **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

### Frequency Rating:

60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

2.813 inches 2.813 inches

#### **Body Width:**

2.688 inches 2.688 inches

#### **Body Height:**

3.313 inches 3.313 inches

#### **Inclosure Type:**

Hermetically sealedhermetically sealed

# **Mounting Facility Quantity:**

4 single group4 single group

# **Mounting Method:**

Threaded stud single groupthreaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group32 single group

# Thread Size:

0.138 inches single group0.138 inches single group

#### **Winding Operating Voltage:**

47.50 ac volts single component single secondary115.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

5 tab, solder lug

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# Demilitarization:

No

#### Fiig:

A058b0