

View Online at <https://aerobasegroup.com/nsn/5950-00-334-9314>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.750 inches

Body Width:

3.620 inches

Body Height:

2.880 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary 10.00 ac volts single component single secondary and 17.00 ac volts single component single secondary and 34.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

25 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0