

View Online at <https://aerobasegroup.com/nsn/5950-00-337-9563>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group1.438 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 320.0 hertz single component and 1.76 kilohertz single component1.76 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.313 inches 2.313 inches

Body Width:

2.063 inches 2.063 inches

Body Height:

2.500 inches 2.500 inches

Inclosure Type:

Openopen

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary and 13.50 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0